

**Plug-In**

**Sunlite 88801 LED CCT PLV Recessed Ballast Bypass Light Bulb, 8 Watt 18W Fluorescent Replacement 950 Lumens, G24d 2 Pin Base, Vertical, UL Listed ROHS Compliant, 3000K - 5000K Tunable Switch, 1 Pack**

Vertical Bypass

**DESCRIPTION:**

Upgrade your fluorescent bulbs with energy efficient LED Sunlite light bulbs. They are instant on at full brightness with no buzzing or flickering. With a life span of up to 50,000 hours you will be required to replace difficult to reach bulbs less often. You will save maintenance costs and save energy at the same time. Features a G24d base. Has multiple color temperature options to choose from 3000K Warm White, 4000K Cool White and 5000K Super White, you can now change color temperatures with just the slide of a switch. Can be used for both commercial and residential locations, these led bulbs are ROHS Certified unlike CFL bulbs they contain no harmful chemicals and do not require special handling or disposal. These LED light bulbs require ballast removal. You must bypass the ballast in all fixtures before installing these bulbs. Simple instructions are available online or consult an electrician for more information



**FEATURES:**

- **UPGRADE TO LED** - Replace your inefficient fluorescent bulbs with energy saving LED bulbs from Sunlite. They are instant on at full brightness with no buzzing or flickering. Can be used in enclosed fixtures and has a High Color Rendering Index rating of 80
- **BALLAST BYPASS REQUIRED** - These LED bulbs do not require a ballast. You must bypass the ballast in all fixtures before installing these bulbs. Simple instructions are included inside the packaging. It can also be found online or consult an electrician for more information
- **ENERGY EFFICIENT** - With a life span of up to 50,000 hours each bulb puts out a bright 950 lumens of light while only using 8 watts of electricity. Annual energy costs are a low \$0.96 (Based on 3 hours/day at \$0.11/kWh)
- **UL LISTED AND ROHS COMPLIANT** - These Sunlite bulbs are UL Listed and have been tested to meet their rigorous safety standards. They are also ROHS Certified unlike fluorescent Bulbs, they contain no harmful chemicals and do not require special handling or disposal
- **TUNABLE COLOR OPTIONS** - With multiple color temperature options you can choose between 3000K Warm White, 4000K Cool White and 5000K Super White. Changing ambience for any application is now easy with just the slide of a switch

## SPECIFICATIONS:

### General Characteristics

<b>Bulb Shape</b>	PLV
<b>Average Rated Hours</b>	50000
<b>Finish</b>	White
<b>Base</b>	2-Pin (G24d)
<b>Average Life Span Years</b>	46
<b>Ingress Protection</b>	IP20 (12.5 mm solids, Not protected from liquids)
<b>Dimmable</b>	No
<b>Material</b>	PC & Aluminum

### Electrical Characteristics

<b>Watts</b>	8
<b>Volts</b>	120-277
<b>Equivalent Wattage</b>	18
<b>LED Chip Manufacturer</b>	2835
<b>Power Factor</b>	0.9
<b>Temperature</b>	-20?~45?

### Light Characteristics

<b>Lumens Brightness</b>	950
<b>Color Rendering Index CRI</b>	80
<b>Emitted Color</b>	CCT Tunable
<b>Color Temperature Kelvin</b>	30/40/50K
<b>Beam Angle</b>	180°
<b>Flicker</b>	Yes

### Additional Features

<b>Safety Rating Mark</b>	UL Listed - Damp Location
---------------------------	---------------------------

### Product Dimensions

<b>MOL (in)</b>	4.66
<b>Diameter (in)</b>	2.12
<b>Item Dimension (in)</b>	(W) 2.12 (H) 4.66 (D) 1.8
<b>Package Dimension (in)</b>	(W) 2.2 (H) 5.3 (D) 1.8
<b>Package Weight (lb)</b>	0.25

### Product Data

<b>Case Unit Rate</b>	12
<b>Pack Size</b>	1
<b>Item UPC</b>	653703888019
<b>Warranty Years</b>	5
<b>Package Type</b>	Box

