

Catalog # 88804-SU PLD/LED/IS/11W/SCT

Plug-In

Sunlite 88804 LED CCT PLD Recessed Plug & Play Light Bulb, 11 Watt 18W Fluorescent Replacement 1025 Lumens, G24d 2 Pin Base Horizontal, Electronic Ballast Compatible 3000K -5000K Tunable Switch 1 Pack

Plug and Play

DESCRIPTION:

Upgrade your fluorescent bulbs with energy efficient LED plug and play light bulbs, a direct replacement with no ballast bypass required. They are instant on at full brightness with no buzzing or flickering. With a life span of up to 50,000 hours you will be required to replace difficult to reach bulbs less often. You'll save maintenance costs and save energy at the same time. Features a G24q base. Has multiple color temperature options to choose from 3000K Warm White, 4000K Cool White and 5000K Daylight you can now change color temperatures with just the slide of a switch. Can be used for both commercial and residential locations, these led bulbs are ROHS Certified unlike CFL bulbs they contain no harmful chemicals and do not require special handling or disposal

FEATURES:

- UPGRADE TO LED replace your inefficient fluorescent bulbs with energy saving LED bulbs from Sunlite. They are instant on at full brightness with no buzzing or flickering. Can be used in enclosed fixtures and has a High Color Rendering Index rating of 80
- PLUG AND PLAY These Sunlite led bulbs replace inefficient fluorescent light bulbs with no bypass required. For use with electronic ballasts only. You can find a complete list of compatible ballasts included in the pdf in this listing
- ENERGY EFFICIENT With a life span of up to 50,000 hours each bulb puts out a bright 1025 lumens of light while only using 11 watts of electricity. Annual energy costs are a low \$1.32 (Based on 3 hours/day at \$0.11/kWh)
- UL LISTED AND ROHS COMPLIANT These Sunlite bulbs are UL Listed and have been tested to meet their rigorous safety standards. They are also ROHS Certified unlike fluorescent bulbs, they contain no harmful chemicals and do not require special handling or disposal
- TUNABLE COLOR OPTIONS with multiple color temperature options you can choose between 3000K Warm White, 4000K Cool White and 5000K Daylight. Changing ambience for any application is now easy with just the slide of a switch



sunlite

SPECIFICATIONS:

General Characteristics

Proc	luct	Dime	nsior	IS
				· •

Bulb Shape	PLD	MOL (in)	5.86
Average Rated Hours	50000	Diameter (in)	1.61
Finish	White	Item Dimension (in)	(W) 5.86 (H) 1.61 (D) 1.22
Base	4-Pin (G24q)	Package Dimension (in)	(W) 6.38 (H) 1.71 (D) 1.35
Average Life Span Years	46	Package Weight (lb)	0.221
Ingress Protection	IP20 (12.5 mm solids, Not protected from liquids)	Product Data	
Dimmable	No	Case Unit Rate	12
Material	PC & Aluminum	Pack Size	1
Electrical Characteristics		Item UPC	653703888040

Electrical Characteristics

Watts	11
Volts	Plug & Play
Equivalent Wattage	18
LED Chip Manufacturer	2835
Power Factor	0.9
Temperature	-4°F - 113°F

Light Characteristics

Color Rendering Index CRI80Emitted ColorCCT TunableColor Temperature Kelvin30/40/50K	Lumens Brightness	1025
	Color Rendering Index CRI	80
Color Temperature Kelvin 30/40/50K	Emitted Color	CCT Tunable
	Color Temperature Kelvin	30/40/50K
Beam Angle 180°	Beam Angle	180°
Flicker Yes	Flicker	Yes

Additional Features

Safety Rating Mark	UL Listed - Damp Location
UL Rated Enclosed Fixtures	Yes
Rohs Compliant	Yes

0.00
1.61
(W) 5.86 (H) 1.61 (D) 1.22
(W) 6.38 (H) 1.71 (D) 1.35
0.221

Case Unit Rate	12
Pack Size	1
Item UPC	653703888040
Warranty Years	5
Package Type	Box

