

Sunlite 88912-SU LED Dual-Head Square Wall Mount Flood Light Fixture With Motion Sensor, 24 Watts, 120 Volts, 2400 Lumen Output, Square Lights, IP65 Rated, ETL Listed, 50K - Super White, Black Finish

## **DESCRIPTION:**

Sunlite LED Square Wall Mount Floodlight fixtures provide ample illumination for all outdoor spaces. Dual heads can be adjusted individually to optimize coverage area. Built-in motion sensor activates lights when movement is detected. With a bright 2400 lumen output at 5000K Super White color temperature they are an energy efficient solution for your lighting needs. Each fixture uses only 24 watts with a low estimated yearly energy cost of \$2.89. (Based on 3 hours/day use at \$0.11/kWh) Ideal for security and entryway lighting in residential or commercial locations. Long life, LED technology built-in means no bulbs to replace and up to 35,000 hours of maintenance-free service. ETL Listed for wet location installation and IP65 rated.

## FEATURES:

- LED TECHNOLOGY Sunlite LED Square Wall Mount Floodlight fixtures provide ample illumination for all outdoor spaces. Each fixture contains 48 high output LEDs and dual heads that can be adjusted individually to optimize coverage area.
- ENERGY EFFICIENT Each fixture uses only 24 watts of energy. Estimated yearly energy cost is a low \$2.89. (Based on 3 hours/day use at \$0.11/kWh) With a 35,000 hour lifespan these fixtures will provide significant savings in electricity over their lifetime and require no maintenance.
- BUILT-IN MOTION SENSOR Built-in motion sensor activates lights when movement is detected.
- SECURITY AND ENTRYWAY LIGHTING Each fixture contains 48 LEDs and gives off a bright 2400 lumen output with 5000K Super White color temperature. Ideal for security and entryway lighting in residential or commercial installations.
- ETL LISTED These fixtures are ETL Listed for wet location installation. They operate on 120 volt service.







## SPECIFICATIONS:

## **General Characteristics**

Average Rated Hours

**Finish** 

Average Life Span Years

**Ingress Protection** 

Dimmable

Lens Material

Lens Finish

Material

**Electrical Characteristics** 

Watts 24

Volts 120

SMD2835 LED Chip Manufacturer **Power Factor** 0.9

.-20°C-45°C **Temperature** 

35000

Black

IP65 (Dust-tight solids, Water

Aluminum & Plastic

Polycarbonate

32

jets)

No

Clear

2400

5000K

Square

2 Wall

LED

Yes

Outdoor

100°

Super White

80

**Light Characteristics** 

Lumens Brightness

Color Rendering Index CRI

**Emitted Color** 

Color Temperature Kelvin

Flicker

Fixture Characteristics

Shape

**Number of Lights** 

Mounting

Fixture Technology

Use Location

Additional Features

Safety Rating Mark

Safety Rated For Canada Safety Rated For USA

Yes

**Product Dimensions** 

Item Dimension (in)

Package Dimension (in)

Package Weight (lb)

**Product Data** 

Case Unit Rate

Item UPC

Warranty Years

(W) 6.06 (H) 11.93 (D) 5.94 (W) 9.1 (H) 6.7 (D) 7.4

1.250

6

653703889122

2

ETL Listed - Wet Location