

# 5-Gallon Pail with Screw Top Lid #A5OVER - 12" dia x 16.75", 1 each/package



Stock this container with sorbents for emergency spill response, or use it to ship damaged containers or hazardous waste.

- DOT-Approved: UN- and DOT-approved container helps companies conform to federal regulations when shipping damaged or leaking containers of hazardous materials, or absorbents contaminated with hazardous substances.
- Perfect for Spill Kits: Stores sorbent products (not included) for easy access as needed for spill control. Saves time when quick response is necessary.
- Sturdy Construction: Pail resists chemicals, rust and corrosion for years of use. Screw-top lid with gasket and built-in torque handle provides sealed, secure closure to prevent leaks and protect contents from moisture, dirt and damage. Durable to withstand rough handling.
- Customized for You: We can customize a Spill Kit to your exact specifications, including the container, its contents and accessories, with no upcharge! Contact your local Distributor for details.

## **A5OVER Specifications**

**Dimensions:** ext. dia. 12" x 16.75" H **Shipping** 15" W x 15" L x 11" H

**Dimensions:** 

Sold as: 1 per package

Color: White

Composition: Polyethylene

Weight: 4.5 lbs. # per Pallet: 72 Incinerable: No

**UN RATING:** 1H2/Y1.5/30

Ship Class: 175

# Metric Equivalent Specifications

**Dimensions:** ext. dia. 30.5cm x 42.5cm H

**Shipping** 38.1cm W x 38.1cm L x 27.9cm H

**Dimensions:** 

Weight: 2 kg



## **A50VER Technical Information**

## Warnings & Restrictions:

There are no known warnings and restrictions for this product.

#### **Regulations and Compliance:**

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

49 CFR 173.12(b)(2)(iv) - When labpacking, "Inner packagings...must be surrounded by a chemically compatible absorbent material in sufficient quantity to absorb the total liquid contents."

49 CFR 173.12(b) - A container used for labpacking must be "a UN 1A2 or UN 1B2 metal drum, a UN 1D plywood drum, a UN 1G fiber drum or a UN 1H2 plastic drum tested and marked at least for the Packing Group III performance level for liquids or solids."

## **Technical Documents:**

(Available at **spilltech.com**)
Product Data Sheet (PDS)

Chemical Compatibility (CCG)

