

## Universal Spill Cart Kit with 8in Wheels #SPKU-CART8 - Absorbs up to 103.2 Gallons



Be prepared for fast response with a SpillTech® Universal Spill Kit!

## SPKU-CART8 Specifications

<b>Dimensions:</b>	31" W x 48" L x 41" H
<b>Shipping Dimensions:</b>	31" W x 48" L x 41" H
<b>Sold as:</b>	1 per package
<b>Absorbency:</b>	Up to 103.2 gal. per package
<b>Weight:</b>	228.77 lbs.
<b># per Pallet:</b>	1
<b>Incinerable:</b>	No
<b>Ship Class:</b>	200
<b>Includes:</b>	160 - 15" x 19" Gray Universal HeavyWeight SonicBonded Pads (GPB100H) 30 - 3" x 4' Gray Universal Sorbent Socks (GCSO430) 10 - 3" x 8' Gray Universal Sorbent Socks (GCSO815) 1 - Emergency Response GuideBook (A-EGB) 4 - 30" x 6" x 60" Yellow Disposal Bags & Ties (A-DISP BAG) 1 - Pair Nitrile Gloves (A-GLV-NIT) 1 - Safety Goggles (A-GOG) 1 - 3" x 5" Vinyl Spill Kit Label (A-KIT LABEL) 1 - 48" x 31" x 48" Yellow Cart with 8" Pneumatic Wheels (A-UTILITYBOX8) 6 - 6" x 2" TamperProof Seals (A-SEAL) 4 - 25/pkg Wipers (WPR500-1)

## Metric Equivalent Specifications

<b>Dimensions:</b>	78.7cm W x 121.9cm L x 104.1cm H
<b>Shipping Dimensions:</b>	78.7cm W x 121.9cm L x 104.1cm H
<b>Absorbency:</b>	Up to 390.6 L per package
<b>Weight:</b>	103.8 kg



**SpillTech**

Online:  
[spilltech.com](http://spilltech.com)

Phone:  
**1-800-228-3877 (N.Am.)**  
**1-770-475-3877 (Other)**

Fax:  
**1-800-872-3764 (N.Am.)**  
**1-770-410-1812 (Other)**

Email:  
[sales@spilltech.com](mailto:sales@spilltech.com)

## SPKU-CART8 Technical Information

### Warnings & Restrictions:

There are no known warnings and restrictions for this product.

### Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

### Technical Documents:

(Available at [spilltech.com](http://spilltech.com))

Product Data Sheet (PDS)



**SpillTech**

Online:  
[spilltech.com](http://spilltech.com)

Phone:  
**1-800-228-3877 (N.Am.)**  
**1-770-475-3877 (Other)**

Fax:  
**1-800-872-3764 (N.Am.)**  
**1-770-410-1812 (Other)**

Email:  
[sales@spilltech.com](mailto:sales@spilltech.com)