

Cable hanger, non-insulated, bolt-on, for 1/2" coaxial cable

Product Description

Hanger, non-insulated, bolt-on for coaxial cable LCF12 / RCF12 / HCA12-50JPL / RHCA12-50, made of stainless steel, kit of 10



Features/Benefits

Stainless steel hangers for supporting elliptical waveguide or coaxial cable to tower. Recommended spacing 1m (3 feet). Hanger may be attached to angle adapters, tower standoffs, member mounting holes with up to M10 or 3/8"-16 hardware or to round member adapters through slot

5.53		
Technical Specifications		
Product Line	Coaxial Cable Accessories	
	Radiating Cable Accessories	
	Elliptical Waveguide Accessories	
	Hybrid Cable Accessories	
Product Type	Hanger	
Hanger Type	Bolt-On, non-insulated	_
Transmission Line Type	LCF12	
	RCF12	
	HCA12-50	
	RHCA12-50	
	HB114	
Cable Type	Air Dielectric	
	Coaxial Foam Dielectric	
	Hybrid	
Cable Size	1/2"	
Number of Cable / Waveguide Runs	1	
Material	Stainless Steel	
Operation Temperature, °C(°F)	-50 to 85 (-58 to 185)	
Storage Temperature, °C(°F)	-50 to 85 (-58 to 185)	
Package Quantity	10	

Notes

Other Documentation