

Power Over Ethernet PoE, Midspan Injector, Category 6a, 1 Port
 10gigabit, 802.3af Certified with Power Supply 56 Volts at 16 Watts



TT-POE10GAF

PoE Injector

Features

- PoE injector, 15.4W, 56V@0.32A Power Over Ethernet IEEE 802.3af certified compliant Type 1
- 10gigabit rated (Category 6a) for up to 55m (180ft); 1gigabit and 5gigabit data rates supported up to 100m (328ft); High quality shielded cabling such as from Transtector's TTE695 line of Ethernet cables is recommended for peak performance
- Midspan type PoE (Power Over Ethernet) Injector with +(1,2)(4,5), -(3,6)(7,8) pin assignments
- Approvals for IEC, EMC, EN, CE and FCC (see data-sheet for full listing)
- Power Supply Included

Applications

- Internet Protocol (IP) and Security Cameras
- Network Switches, Bridges, Access Points, Antennas and Amplifiers
- Voice over Internet Protocol (VOIP) Telephones
- Traffic Systems
- Building Control Systems and Digital Signage

Description

The TT-POE10GAF PoE injector from Transtector is IEEE 802.af certified and is here to meet all your Ethernet power requirements. Its one port shielded design can supply up to 15.4 watts and 56 volts at 0.32 amps of power to your power over Ethernet device. Transtector's TT-POE10GAF is excellent for security cameras, access points, IP phones, network switches, digital signage, building, lighting, traffic control systems or any PoE Type 1 IEEE 802.af compliant equipment.

Transtector's TT-POE10GAF midspan injector is certified for up to 10gig speeds (Category 6a) for up to 55m (180ft). 1gig and 5gig speeds are supported to up to 100m (328ft). High quality Ethernet cables such as from Transtector's TTE695A line are recommended for peak performance. The power supply is included with each Power Over Ethernet PoE 15.4 watts and 56 volts Midspan Injector unit.

The TT-POE10GAF PoE injector is certified for various IEC, EMC, EN and FCC regulations (see datasheet for full details) and is CE listed. It's simple and compact design is easy to use and set up. This Transtector's Power Over Ethernet PoE Category 6a in stock and ships same day, Contact Transtector today with your project requirements.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Ethernet Connectors		RJ45 Jack		
PoE Version		802.3af		
Ethernet Standard		Category 6, 10/100/1000Base-T		
Max Current			0.32	A
Voltage Rating DC (Input)			240	VDC
Voltage Rating DC (Output)			56	VDC
Operating Voltage AC			264	VAC

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Power Over Ethernet PoE, Midspan Injector, Category 6a, 1 Port 10gigabit, 802.3af Certified with Power Supply 56 Volts at 16 Watts](#)

Power Over Ethernet PoE, Midspan Injector, Category 6a, 1 Port
 10gigabit, 802.3af Certified with Power Supply 56 Volts at 16 Watts



TT-POE10GAF

PoE Injector

Power Connector	2.5mm DC Jack
-----------------	---------------

Electrical Specification Notes:

10Gb distance may vary according to the cable and data source used. Shielded, high quality network cable is recommended such as Transtector's TTE695A line. Category 6a/7, 10Gb distances are supported up to 180ft (55m) with 1Gb and 5Gb distances supported up to 328ft (100m) when using appropriate cabling.

Mechanical Specifications

Size

Height	2 in	[50.8 mm]
Width	2 in	[50.8 mm]
Length	4 in	[101.6 mm]
Weight	0.265 lbs	[120.2 g]
Housing Material	Aluminum	

Environmental Specifications

Operating Temperature, Injector	0 to +40 deg C
Environment Type	Indoor
EMI, EMC, EN Compliance	Yes per EMC Directive 2014/30/EU with compliance to EN 55032:2015, EN55035:2017, EN 61000-3-2:2019, EN61000-3-3:2013+A1:2019, & EN 62368-1:2014+A11:2017
FCC Compliant	Yes per Part 15, Subpart B Class B, ANSI C63.4:2014
CE-LVD Marking	Yes per LVD 2014/35/EU

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Power Over Ethernet PoE, Midspan Injector, Category 6a, 1 Port 10gigabit, 802.3af Certified with Power Supply 56 Volts at 16 Watts](#)

URL: <https://www.transtector.com/poe-injector-category-6-1-port-rj45-jack-tt-poe10gaf-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

CAD Drawing


REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	08/26/2020	GUTTADAURO



NOTES:

1. PRODUCT SHALL BE INDIVIDUALLY PACKAGED.
2. PACKAGED WITH 1X US STYLE POWER CORD, 0.6M IN LENGTH.
3. SEE LABEL SPECIFICATION ILS-100. FOR INTERNAL REFERENCE ONLY.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS; DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED, LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS		THIRD-ANGLE PROJECTION	
<div></div>		<div></div>	
TOLERANCES:		THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF TRANSTECTOR, INC. ALL RIGHTS RESERVED.	
X = ± .2 [.508]	FRACTIONS XX = ± .02 [.51] XXX = ± .005 [.13]	an INFINIT@ brand	
ANGLES ± °		10701 Airport Road, Hayden, ID 83835	
CABLE LENGTH (L) TOLERANCES:		Phone: 1.208.635.9400 1.800.882.9110	
L ≤ 12 [305] = +1 [25] / -0		Fax: 1.208.955.2041	
12 [305] < L ≤ 60 [1524] = +2 [51] / -0		Website: www.transductor.com	
60 [1524] < L ≤ 120 [3048] = +4 [102] / -0		E-mail: sales@transductor.com	
120 [3048] < L ≤ 300 [7620] = +6 [152] / -0		ITEM NO.	
300 [7620] < L = +5% / -0		DRAWN BY	
ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.		CAGE CODE	
		DZINN	
		30992	
		SIZE	
		A	
		SCALE	
		1 OF 1	
		SHEET	
		N/A	
		REV	
		A	
		TT-POE10GAF	