



SSH-M

SnapStak® Plus Adjustable Hanger for 15mm to 26mm Cable - No Grommets Required

Product Classification

Brand	SnapStak® Plus
Product Type	Hanger kit

Dimensions

Compatible Diameter, maximum	26.000 mm 1.024 in
Compatible Diameter, minimum	15.000 mm 0.591 in
Height	67.10 mm 2.64 in
Length	48.60 mm 1.91 in
Width	38.00 mm 1.50 in

Electrical Specifications

DTF Effect	0.1 dB
Return Loss Effect	0.1 dB

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
-----------------------	--------------------------------------

General Specifications

Hanger Type	Snap-in hanger
Cables per Hanger	1
Color	Silver
CommScope Accessories	Hangers
Material Type	Stainless steel
Maximum Stack Height	2
Maximum Stack Height, Coaxial	3
Ordering Note	CommScope® standard product in the United States and Canada
Package Quantity	10

Mechanical Specifications

Corrosion Resistance, minimum with no degradation	=1000 hours in salt spray chamber
Flammability Test Method	UL 2043
Mounting	3/4 in drilled cable ladder

SSH/M

Vibration Survival =4 hours at resonant frequency
Environmental Strength Capability Double cable weight

Packed Dimensions

Height	330.2 mm 13.0 in
Length	260.4 mm 10.3 in
Shipping Weight	0.53 kg 1.17 lb
Width	63.5 mm 2.5 in

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

* Footnotes

Maximum Stack Height Fiber, Hybrid, Power