

MD356 SERIES Mobile duplexer, 6 cavity, N female connector, 380-480 MHz

- Compact and rugged design, ideal for mobile applications
- Low insertion loss for optimal system performance
- High isolation to minimize interference

MD356 series is Sinclair's new line of mobile duplexer that features six resonators for outstanding performance. This duplexer allows bi-directional communication over a common antenna and is ideal for applications that call for a compact rugged unit, such as in vehicles, or where space is constrained.

The Tx and Rx frequency separation available is 5 or 10 MHz. See below chart for detailed ordering information, and specify Tx and Rx frequencies when ordering. Other connector types are also available, please call for details.



N female connector model shown. Image for illustration only and may not be an exact representation of product.

Part#	Connector	Frequency range	Separation
MD356N-1-1	N(f)	406-440 MHz	5 MHz
MD356N-1-2	N(f)	406-440 MHz	10 MHz
MD356N-2-1	N(f)	440-480 MHz	5 MHz
MD356N-2-2	N(f)	440-480 MHz	10 MHz
MD356N-4-1	N(f)	380-400 MHz	5 MHz
MD356N-4-2	N(f)	380-400 MHz	10 MHz

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet		MD356 SERIES	Issue: 0	Dated: 04-20-20

Electrical Specifications

Frequency Range	MHz	380 to 480
Number of Cavities - Low Pass Side		3
Number of Cavities - High Pass Side		3
Connectors		N-female
Input VSWR (max)		1.5:1
Insertion loss (max)	dB	1.4
Impedance	Ω	50
Average Input Power (max)	W	50
Isolation (min)	dB	75

Mechanical Specifications

Width	in (mm)	6.05 (154)
Depth	in (mm)	8.92 (227)
Length/ Height	in (mm)	1.13 (28.7)
Weight	lbs (kg)	2.7 (1.23)
Mounting configurations		mounting holes provided
Actual shipping weight	lbs (kg)	3.1 (1.41)
Shipping dimensions	in (mm)	13x9x3 (330x229x76)


Environmental Specifications

Temperature range	°F (°C)	-22 to +140 (-30 to +60)
-------------------	---------	--------------------------

Notes

Ordering Information

Specify Tx and Rx frequencies when ordering.



Typical response curve for 5 MHz separation

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet		MD356 SERIES	Issue: 0	Dated: 04-20-20