



## 12" x 10" x 5" Single Line PoE Heated & Cooled Wi-Fi Enclosure Solution for 2702e/3702e/2802e/3802e Cisco Access Points

Ventev's PoE Powered Outdoor Enclosure System is a plug-and-play solution engineered to enable the use of Cisco 2802e and 3802e series access points in outdoor applications. Housed in a 12"x10"x5" Sleek NEMA enclosure, this compact system includes a controlled heating and cooling system that keeps ambient temperature of the enclosure within manufacturer specified operating temperature. This system can utilize an integrated Omni antenna, or an external Patch or Omni antenna mounted separately. A single PoE line powers both the AP and the heating and cooling system.

*Every Ventev enclosure is covered by the company's two-year TerraNet warranty program. For questions or to purchase product, contact a Regional Sales Executive at 410-229-1201, 800-851-4965 or sales@ventev.com.*



Single Line PoE Heated & Cooled w/o Integrated Antenna  
Part #: VNV-OUT3802-AC  
SKU: 236375



Single Line PoE Heated & Cooled w/ Integrated Antenna  
Part #: VNV-OUTA3802-AC  
SKU: 278456

### Features

- Compatible with the 2702e/3702e and 2802e/3802e APs
- Compact, durable, weatherproof, NEMA-3RX rated outdoor enclosure, constructed of a high-quality polycarbonate plastic that is UV resistant, corrosion resistant and sustainable in broad temperature ranges
- Innovative heating & cooling system, powered by a single PoE line that powers both the AP and environmental elements

### Benefits

- Extend Wi-Fi outdoors at a lower cost, using an indoor Cisco AP and a Ventev outdoor enclosure solution (vs. an outdoor AP)
- Protect the AP from theft, tampering and impact with a secure, durable Polycarbonate enclosure
- Protect the AP from harsh environmental elements (heat/cold, rain/sleet/snow/ice, corrosion) with a NEMA-3RX rated enclosure
- Eliminate the need for costly AC power deployment, midspan PoE injectors and the need for additional switch ports with a single line PoE-only powered solution
- Ensure **aesthetically-pleasing** appearance with a compact fully-integrated solution



## 12" x 10" x 5" Single Line PoE Heated & Cooled Wi-Fi Enclosure Solution for 2702e/3702e/2802e/3802e Cisco Access Points

### PoE Heated & Cooled Enclosure Specifications

<b>Dimensions (W x L x H)</b>	12" x 10" x 5"
<b>Enclosure Material</b>	Polycarbonate
<b>Color</b>	Grey
<b>NEMA Rating</b>	3RX
<b>Environmental Temp Range</b>	-22°F to 104°F (-30° to 40° C)
<b>Heating</b>	12 VDC, 8 Watt (Heat)
<b>Heating Thermostat Operation</b>	On: 41°F (5°C), Off: 59°F (15°C)
<b>Cooling</b>	30.4 CFM, 12 VDC Fan
<b>Cooling Thermostat Operation</b>	On: 122°F (50°C), Off: 95°F (35°C)
<b>Input Power</b>	Single 25.5 PoE Line
<b>AP Minimum Operating Temp</b>	Greater than or equal to -4°F (-20°C)
<b>AP Maximum Operating Temp</b>	Less than or equal to 50°F (122°C)
<b>Weight</b>	10 lbs

### Single Line PoE Heated & Cooled Enclosure SKU Numbers

	Solid Door w/o Integrated Omni Antenna	Solid Door w/ Integrated Omni Antenna
<b>SKU #</b>	236375	278456
<b>Part #</b>	VNV-OUT3802-AC	VNV-OUTA3802-AC