

# ASP705K

---



1-port omni antenna, 450–470 MHz, 360° HPBW, fixed electrical tilt

- Invert mountable

## General Specifications

<b>Antenna Type</b>	Omni
<b>Band</b>	Single band
<b>Color</b>	Off-white
<b>Grounding Type</b>	RF connector inner conductor and body grounded to reflector and mounting bracket
<b>Performance Note</b>	Outdoor usage
<b>Radome Material</b>	Fiberglass, UV resistant
<b>Radiator Material</b>	Brass
<b>RF Connector Interface</b>	N Female
<b>RF Connector Location</b>	Bottom
<b>RF Connector Quantity, low band</b>	1
<b>RF Connector Quantity, total</b>	1

## Dimensions

<b>Length</b>	5588 mm   220 in
<b>Outer Diameter</b>	76.2 mm   3 in

## Electrical Specifications

<b>Impedance</b>	50 ohm
<b>Polarization</b>	Vertical

## Electrical Specifications

<b>Frequency Band, MHz</b>	<b>450–470</b>
<b>Gain, dBi</b>	12.1
<b>Beamwidth, Horizontal, degrees</b>	360

# ASP705K

---

<b>Beamwidth, Vertical, degrees</b>	7
<b>Beam Tilt, degrees</b>	0
<b>VSWR   Return loss, dB</b>	1.5   14.0
<b>Input Power per Port, maximum, watts</b>	500

## Mechanical Specifications

<b>Wind Loading at Velocity, maximum</b>	364.8 N @ 100 mph   82.0 lbf @ 100 mph
<b>Wind Speed, maximum</b>	201 km/h   124.896 mph

## Packaging and Weights

<b>Net Weight, without mounting kit</b>	10 kg   22.046 lb
---	-------------------

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system



## Included Products

ASPR616 — Pipe Mounting Kit for 1.25 - 3.5 in (35 - 89.0 mm) OD round members

## \* Footnotes

<b>Performance Note</b>	Severe environmental conditions may degrade optimum performance
-------------------------	---