

INSTALLATION INSTRUCTIONS

Product

Revision

<u>Form</u>

7160-0177, 7160-0178

Rev D

NST-412

Center Upper Pole Assemblies - 5" & 7"

Printing Spec: PS-001

The Center Upper Pole Assemblies are used with any DS Lower Tubes or DS Vehicle Bases with an integrated lower tube.

Remove the (4) .25x 20 x .625 hex head flange bolts holding the upper bracket to the tube.


Assemble the Motion Attachment device being used to the upper bracket.

Reattach the upper bracket to the tube with the (4) .25x 20 x .625 hex head flange bolts that were previously removed.

Insert the Center Upper Pole Assembly into the Lower Tube or the Vehicle Base being used.

While holding the Center Upper Pole Assembly at the desired position, tighten the center bolt securely with a 9/16" open-end wrench.

Two 3/8" dia holes are provided as a strain relief tie down points for use with a security cable.



Product Mounting Disclaimer

Gamber-Johnson is not liable under any theory of contract or tort law for any loss, damage, personal injury, special, incidental or consequential damages for personal injury or other damage of any nature arising directly or indirectly as a result of the improper installation or use of its products in vehicle or any other application. In order to safely install and use Gamber-Johnson products full consideration of vehicle occupants, vehicle systems (i.e., the location of fuel lines, brakes lines, electrical, drive train or other systems), air-bags and other safety equipment is required. Gamber-Johnson specifically disclaims any responsibility for the improper use or installation of its products not consistent with the original vehicle manufactures specifications and recommendations, Gamber-Johnson product instruction sheets, or workmanship standards as endorsed through the Gamber-Johnson Certified Installer Program.

© Copyright 2020 Gamber-Johnson, LLC