



The NLOS series antenna system offered by Laird Connectivity is constructed of stainless steel for outstanding service life. Individual elements are welded to the main beam for permanent attachment. Welded elements give more consistent signal performance because they ensure high conductivity across the antenna surface. These antennas have high gain and good front-to-back performance to minimize external interference. They can be mounted in vertical or horizontal polarization. They come standard with an 18-inch pigtail cable terminated with an N-female connector. Other connector types are available upon request.

FEATURES AND BENEFITS

- High-gain directional antenna
- Available in 9, 11, and 13 dBi gain models
- Stainless steel construction, low wind loading
- Simple installation – Vertical or horizontal polarization
- 18-inch pigtail with Type N-female connector (standard)
- DC ground for lightning protection

APPLICATIONS

- 900 MHz ISM band applications
- Non-line-of-sight applications
- WISP CPE equipment
- Cellular applications
- Utility transmission and distribution communications.

ELECTRICAL SPECIFICATIONS

Model Name	YA9-9	YA9-11	YA9-13
Operating Frequency (MHz)	860-960		
VSWR	1.5:1		
Nominal Impedance (Ohms)	50		
Max Power - Ambient 25°C (W)	100		
Gain (dB)	9	11	13
Number of Elements	5	8	15
3 dB Beamwidth	53°	50°	30°
Front-to-Back Ratio (dB)	>14	>15	>18
Gamma Match Type	Internally matched		

MECHANICAL SPECIFICATIONS

Model Name	YA9-9	YA9-11	YA9-13
Length Dimensions m(in); [Note element width ~ 152 mm (6 in.)]	0.5 (19.7)	0.9 (35.4)	1.45 (57.0)
Weight – kg (lbs.)	0.7 (1.9)	0.9 (2.4)	1.25 (3.3)
Pole Size – mm (in.)	25 to 51 (1 to 2)		
Element Construction	Welded		
Bracket Included	Included		
Mounting	Up to 2.5-inch diameter mast		


ENVIRONMENTAL SPECIFICATIONS

Operating Temperature – °C (°F)	-45 to +70°C (-49 to +158°F)		
Rated Wind Velocity – m/sec (mph)	56 (125)		
Wind Loading – lbs.	YA9-9	YA9-11	YA9-13
Square Inch	19	29	45
100 MPH	4.75	7.25	11.3
125 MPH	7.42	11.3	17.6
100 MPH with ½-inch radial ice	8.0	12.0	21.0
Material Substance Compliance	RoHS		


CONFIGURATION

PART NUMBER	DESCRIPTION
YA9-9	9 dB NLOS series 900 MHz Yagi antenna with N-female connector
YA9-11	11 dB NLOS series 900 MHz Yagi antenna with N-female connector
YA9-11-RTNC-48	11 dB NLOS series 900 MHz Yagi antenna with RPTNC connector
YA9-13	13 dB NLOS series 900 MHz Yagi antenna with N-female connector


RADIATION PATTERNS




YA9-9
E-Plane




YA9-11
E-Plane




YA9-13
E-Plane



YA9-9
H-Plane



YA9-11
H-Plane



YA9-13
H-Plane

sales@lairdconnect.com
support@lairdconnect.com
www.lairdconnect.com



Laird Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird Connectivity product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

Any information furnished by Laird Connectivity and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Connectivity materials rests with the end user, since Laird Connectivity and its agents cannot be aware of all potential uses. Laird Connectivity makes no warranties as to the fitness, merchantability or suitability of any Laird Connectivity materials or products for any specific or general uses. Laird Connectivity shall not be liable for incidental or consequential damages of any kind. All Laird Connectivity products are sold pursuant to the Laird Connectivity Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2021 Laird Connectivity All Rights Reserved. Laird Connectivity, the Laird Connectivity logo, and other marks are trademarks or registered trademarks of Laird Connectivity or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Connectivity or any third-party intellectual property rights.

