

Lace-up Hoisting Grip for 1/2 in coaxial cable and elliptical waveguide
180 and 220



Product Classification

Product Type	Hoisting grip
Ordering Note	CommScope® standard product in the United States and Canada

General Specifications

Attachment Spacing Intervals	60.96 m 200 ft
Hoisting Grip Type	Lace-up hoisting grip
Support Clamp	Not included
Tool Type	Hoisting grip

Dimensions

Grip Length, minimum	254 mm 10 in
Leader Length, minimum	177.8 mm 7 in
Nominal Size	1/2 in

Electrical Specifications

Return Loss Effect	0.1 dB
DTF Effect	0.1 dB

Material Specifications

Material Type	Stainless steel
----------------------	-----------------

Mechanical Specifications

Pull Load Capacity	226.796 kg 500 lb
---------------------------	---------------------

Packaging and Weights

43094

Height, packed	43.18 mm 1.7 in
Width, packed	187.96 mm 7.4 in
Length, packed	246.38 mm 9.7 in
Packaging quantity	1
Weight, gross	0.2 kg 0.441 lb

Regulatory Compliance/Certifications

Agency

CHINA-ROHS

ISO 9001:2015

REACH-SVHC

ROHS

Classification

Below maximum concentration value

Designed, manufactured and/or distributed under this quality management system

Compliant as per SVHC revision on www.commscope.com/ProductCompliance

Compliant

