



Cold shrink Kit for 1/2 in through 3/8 in cable to 1/2 in through 3/8 in cable

Product Classification

Product Type	Cold shrink kit
Ordering Note	CommScope® non-standard product

General Specifications

Application	Provides additional moisture seal for cable connections
Applications per Kit	One 1/2 in–3/8 in to 1/2 in–3/8 in
Cable Family	AL5-50 AVA5-50 FSJ4-50B FSJ4-75A LDF4-50A LDF4-75 LDF5-50A LDF5-75 VXL5-50
Color	Black

Dimensions

Length	202.946 mm 7.99 in
Cable Diameter for Seal, maximum	21.34 mm 0.84 in
Cable Diameter for Seal, minimum	7.37 mm 0.29 in
Inner Diameter	53.09 mm 2.09 in
Nominal Size	1/2 in 3/8 in

Material Specifications

Material Type	EPDM rubber
----------------------	-------------

Environmental Specifications

UV Resistance Test Method	UV condensation reference ASTM-G-53, light source UVA 340 fluorescent lamp
UV Resistance, minimum with no degradation	≥1000 hours
Weather Resistance Test Method	04AS00-03.6.0 MIL-STD-1344A, Method 1002

245173

Packaging and Weights

Height, packed	299.72 mm 11.8 in
Width, packed	76.2 mm 3 in
Length, packed	76.2 mm 3 in
Included	One EPDM rubber tube One sealing foam strip
Packaging quantity	1
Weight, gross	0.14 kg 0.309 lb

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

