

Universal Snap-in Hanger for elliptical waveguide 77

Product Classification

Product Type Hanger kit

General Specifications

 Cable Type
 Elliptical waveguide

Cables per Hanger

Color Silver

Hanger TypeSnap-in hangerMounting3/4 in through hole

Dimensions

 Height
 40.894 mm | 1.61 in

 Width
 51.054 mm | 2.01 in

 Length
 82.042 mm | 3.23 in

 Compatible Diameter, maximum
 30.988 mm | 1.22 in

 Compatible Diameter, minimum
 26.67 mm | 1.05 in

 Waveguide Size
 WR112 | WG15 | R84

Electrical Specifications

Return Loss Effect 0.1 dB
DTF Effect 0.1 dB

Material Specifications

Material Type Stainless steel

Mechanical Specifications

Vibration Survival ≥4 hours at resonant frequency

Page 1 of 2



EWSH-77

Environmental Specifications

Operating Temperature $-40 \,^{\circ}\text{C}$ to $+85 \,^{\circ}\text{C}$ ($-40 \,^{\circ}\text{F}$ to $+185 \,^{\circ}\text{F}$)

Corrosion Resistance, minimum with no degredation ≥500 hours in salt spray chamber

Environmental Strength Capability Double cable weight

Packaging and Weights

 Height, packed
 20 cm
 7.874 in

 Width, packed
 20 cm
 7.874 in

 Length, packed
 20 cm
 7.874 in

Packaging quantity 10

Weight, gross 1.6 kg | 3.527 lb

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant





