

POWERED BY



FJ-4SM-008-10M

**Bend Insensitive Singlemode Fiber LC to LC 4-Fiber Distribution Cable, riser, black jacket, 10 m**

## Construction Materials

Fiber Type	Bend insensitive singlemode fiber (G.657.A1)
Total Fibers, quantity	4
Jacket Color	Black

## Dimensions

Cord Length	10.0 m   32.8 ft
Breakout Length, Fiber, end 1	700 mm   28 in
Breakout Length, Fiber, end 2	200 mm   8 in

## Environmental Specifications

Environmental Space	Wireless installation
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

## General Specifications

Construction Type	Discrete fiber tail
Cable Glands	No glands
Color, Channel 1	Blue
Color, Channel 2	Orange
Interface Feature, connector A	Standard
Interface Feature, connector B	Standard
Interface, connector A	LC
Interface, connector B	LC
Minimum Bend Radius, furcation	30.0 mm   1.2 in
Pulling Grips, quantity	1

## Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system



## Included Products

760170993 | Z-004-MP-8F-M60BK (Product Component—not orderable) — Indoor/Outdoor Low Smoke Zero Halogen

FJ-4SM-008-10M



Riser MPO Trunk Cable, 4 fiber

- CS-8F-MP (Product Component—not orderable) — Low Macrobending, Zero Water Peak, Dispersion-Unshifted Singlemode Fiber