

SSH-158-3

SnapStak® Hanger for 1-5/8 in coaxial cable, triple stack capability, includes reinforcement bar



Product Classification

Product Type	Hanger kit
Product Brand	SnapStak®
Ordering Note	CommScope® standard product in the United States and Canada

General Specifications

Cables per Hanger	1
Color	Silver
Hanger Type	Snap-in hanger
Mounting	3/4 in drilled cable ladder

Dimensions

Height	40.894 mm 1.61 in
Maximum Stack Height	3
Width	50.8 mm 2 in
Length	89.916 mm 3.54 in
Compatible Diameter, maximum	52.07 mm 2.05 in
Compatible Diameter, minimum	48.26 mm 1.9 in
Nominal Size	1-5/8 in

Electrical Specifications

Return Loss Effect	0.1 dB
DTF Effect	0.1 dB

Material Specifications

Material Type	Stainless steel
---------------	-----------------

SSH-158-3

Mechanical Specifications

Vibration Survival ≥4 hours at resonant frequency

Environmental Specifications

Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F)

Corrosion Resistance, minimum with no degradation ≥500 hours in salt spray chamber

Environmental Strength Capability Double cable weight

Packaging and Weights

Height, packed 22 cm | 8.661 in

Width, packed 15 cm | 5.906 in

Length, packed 14.4 cm | 5.669 in

Packaging quantity 10

Weight, gross 0.6 kg | 1.323 lb

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant



* Footnotes

Maximum Stack Height Fiber, Hybrid, Power