

BHD-78



Double Block Hanger for 7/8 in coaxial cable

Product Classification

Product Type	Hanger kit
Ordering Note	CommScope® standard product in the United States and Canada

General Specifications

Cables per Hanger	2
Color	Black
Hanger Type	Double block hanger
Mounting	3/8 in (M10) drilled cable ladder

Dimensions

Height	42.926 mm 1.69 in
Maximum Stack Height	3
Width	40.132 mm 1.58 in
Length	80.01 mm 3.15 in
Compatible Diameter, maximum	28.194 mm 1.11 in
Compatible Diameter, minimum	27.686 mm 1.09 in
Nominal Size	7/8 in

Electrical Specifications

Return Loss Effect	0.1 dB
DTF Effect	0.1 dB

Material Specifications

Material Type	30% glass filled polypropylene (PP)
----------------------	-------------------------------------

BHD-78

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Environmental Strength Capability	Double cable weight
UV Resistance, minimum with no degradation	≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

Height, packed	5.1 cm 2.008 in
Width, packed	17.8 cm 7.008 in
Length, packed	22.9 cm 9.016 in
Packaging quantity	10
Weight, gross	0.56 kg 1.235 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant



* Footnotes

Maximum Stack Height Fiber, Hybrid, Power