

BHD-12



Double Block Hanger for 1/2 in coaxial cable (LDF4)

Product Classification

Product Type

Hanger kit

Ordering Note

CommScope® standard product in the United States and Canada

General Specifications

Cables per Hanger

2

Color

Black

Hanger Type

Double block hanger

Mounting

Mounting hole clearance for 3/8, 16 UNC or M10 threaded rod

Dimensions

Height

40.132 mm | 1.58 in

Maximum Stack Height

3

Width

33.02 mm | 1.3 in

Length

67.056 mm | 2.64 in

Compatible Diameter, maximum

16.256 mm | 0.64 in

Compatible Diameter, minimum

15.494 mm | 0.61 in

Nominal Size

1/2 in

Electrical Specifications

Return Loss Effect

0.1 dB

DTF Effect

0.1 dB

Material Specifications

Material Type

30% glass filled polypropylene (PP)

BHD-12

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Environmental Strength Capability	Double cable weight
UV Resistance, minimum with no degradation	≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

Height, packed	3.8 cm 1.496 in
Width, packed	17.8 cm 7.008 in
Length, packed	25.4 cm 10 in
Packaging quantity	10
Weight, gross	0.37 kg 0.816 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant



* Footnotes

Maximum Stack Height Fiber, Hybrid, Power