



INDOOR/OUTDOOR

INDOOR/OUTDOOR
TIGHT BUFFER

ezDISTRIBUTION™ I/O Tight Buffered Riser and plenum cables



This versatile indoor-outdoor flame-rated cable design combines standards compliant performance with the direct connectorization simplicity afforded by tight buffered fibers. These cables provide an effective solution for interbuilding and building transition applications utilizing field installable connectors.

Overview

Prysmian's ezDISTRIBUTION cable family packages up to 144 color-coded 900 µm tight buffered fibers into a single flame retardant cable. This cable design is available in both riser rated and plenum rated versions for deployment in any inside plant fire-code application. The UV-resistant outer jacket, coupled with dry water blocking technology, address environmental concerns for outdoor use. The tight buffered distribution cable supports standard installation practices and may be easily terminated using established field connectorization methods.

Product Snapshot

Applications	Versatile indoor-outdoor tight buffered cable for use with field installable connectors.
Constructions	Single-Unit ($\leq 24f$); subunits ($\geq 18f$); interlock armor optional
Flame Ratings	Riser (OFNR / OFCR / FT4); Plenum (OFNP / OFCP / FT6)
Fiber Count	2 to 144 fibers (Riser)/2 to 96 (Plenum)
Fiber Types	Single-mode (ESMF, bend-insensitive) multimode (62.5/125-OM1, 50/125- OM2+, OM3 & OM4)
Standards	TIA/EIA-568, ANSI/ICEA S-83-596, ANSI/ICEA S-104-696, UL-1666, NFPA 262, CSA 22.2 Telcordia GR-409, Telcordia GR-20, RoHS Compliant

Feature and Benefits

- 900 µm tight buffered fibers designed to support rapid field termination
- Industry standard color coding for quick, error-free fiber identification
- Single-unit designs provide space savings and cost advantages
- Subunit construction improves organization and termination practices
- Available with bend-insensitive single-mode and multimode optical fibers
- Flexible, flame-retardant and UV-stable outer jacket
- Optional Interlock armor provides robust protection and supports one-step installation
- Supports all high performance networks including OM4/10 gigabit ethernet systems



ezDISTRIBUTION™ I/O Tight Buffered

Riser and plenum cables



ezDISTRIBUTION | Indoor-Outdoor Riser | C1181 Series | OFNR/FT4

Fiber Count	Fibers Per Subunit	Diameter inches (mm)	Cable Weight lb/kft (kg/km)	Bend Radius Load inches (cm)	Bend Radius No Load inches (cm)	Max Installation Load (Pull Strength) lbs (newtons)	Max Operation Load lbs (newtons)
2	single-unit	0.19 (4.8)	15 (22)	3.8 (9.7)	1.9 (4.9)	100 (445)	30 (133)
4	single-unit	0.22 (5.6)	19 (28)	4.4 (11.2)	2.2 (5.6)	100 (445)	30 (133)
6	single-unit	0.24 (6.0)	21 (31)	4.8 (12.2)	2.4 (6.1)	100 (445)	30 (133)
8	single-unit	0.25 (6.2)	23 (34)	5.0 (12.7)	2.5 (6.4)	100 (445)	30 (133)
12	single-unit	0.28 (7.0)	30 (45)	5.6 (14.3)	2.8 (7.2)	150 (666)	45 (200)
18	single-unit	0.31 (7.7)	36 (53)	6.1 (15.5)	3.0 (7.6)	300 (1335)	90 (400)
24	single-unit	0.32 (8.1)	43 (64)	6.4 (16.3)	3.2 (8.2)	300 (1335)	90 (400)
18	6	0.53 (13.5)	103 (153)	11.2 (28.5)	5.6 (14.3)	600 (2670)	180 (801)
24	6	0.53 (13.5)	103 (153)	11.2 (28.5)	5.6 (14.3)	600 (2670)	180 (801)
36	6	0.66 (16.8)	160 (238)	13.2 (33.6)	6.6 (16.8)	600 (2670)	180 (801)
48	12	0.66 (16.8)	140 (209)	13.2 (33.6)	6.6 (16.8)	600 (2670)	180 (801)
60	12	0.74 (18.8)	171 (254)	14.8 (37.6)	7.4 (18.8)	600 (2670)	180 (801)
72	12	0.80 (20.3)	208 (309)	16.0 (40.7)	8.0 (20.4)	600 (2670)	180 (801)
96	12	0.95 (24.2)	296 (441)	19.0 (48.3)	9.5 (24.2)	600 (2670)	180 (801)
144	12	1.02 (25.9)	347 (516)	20.4 (51.9)	10.2 (25.9)	600 (2670)	180 (801)

Note: Cable damage may occur if installation temperature limits are exceeded; therefore, Prysmian Group recommends storing I/O cables in appropriate temperature conditions ≥ 24 hours prior to placement.

Temperature Range

Shipping and Storage: (Riser) -40° F to +176° F (-40° C to +80° C)
 (Plenum) -40° F to +176° F (-40° C to +80° C)

Installation: (Riser) +14° F to +140° F (-10° C to +60° C)
 (Plenum) +32° F to +140° F (0° C to +60° C)

Operation: (Riser) -40° F to +176° F (-40° C to +80° C)
 (Plenum) -40° F to +176° F (-40° C to +80° C)

INDOOR/OUTDOOR

ezDISTRIBUTION™ I/O Tight Buffered

Riser and plenum cables



ezDISTRIBUTION | Indoor-Outdoor Plenum | C1182 Series | OFNP/FT6

Fiber Count	Fibers Per Subunit	Diameter inches (mm)	Cable Weight lb/kft (kg/km)	Bend Radius Load inches (cm)	Bend Radius No Load inches (cm)	Max Installation Load (Pull Strength) lbs (newtons)	Max Operation Load lbs (newtons)
2	single-unit	0.18 (4.5)	9 (13)	3.6 (9.2)	1.8 (4.6)	100 (445)	30 (133)
4	single-unit	0.18 (4.6)	14 (21)	3.6 (9.2)	1.8 (4.6)	100 (445)	30 (133)
6	single-unit	0.20 (5.0)	15 (22)	4.0 (10.2)	2.0 (5.1)	100 (445)	30 (133)
8	single-unit	0.20 (5.2)	18 (27)	4.0 (10.2)	2.0 (5.1)	100 (445)	30 (133)
12	single-unit	0.24 (6.1)	22 (33)	4.8 (12.2)	2.4 (6.1)	150 (666)	45 (199.8)
18	single-unit	0.26 (6.5)	32 (48)	5.1 (13.0)	2.6 (6.5)	150 (666)	45 (199.8)
24	single-unit	0.30 (7.6)	42 (62)	6.0 (15.3)	3.0 (7.7)	150 (666)	45 (199.8)
18	6	0.41 (10.4)	86 (128)	8.2 (20.9)	4.1 (10.5)	400 (1800)	120 (540)
24	6	0.41 (10.4)	79 (117)	8.2 (20.9)	4.1 (10.5)	400 (1800)	120 (540)
36	6	0.54 (13.9)	132 (196)	10.8 (27.5)	5.4 (13.8)	400 (1800)	120 (540)
48	12	0.55 (13.9)	140 (209)	11.0 (28.0)	5.5 (14.0)	400 (1800)	120 (540)
60	12	0.63 (16.0)	173 (257)	12.6 (32.0)	6.3 (16.0)	400 (1800)	120 (540)
72	12	0.65 (16.6)	210 (312)	13.0 (33.1)	6.5 (16.6)	600 (2670)	180 (801)
96	12	0.84 (21.3)	345 (514)	16.8 (42.7)	8.4 (21.4)	600 (2670)	180 (801)

Note: Cable damage may occur if installation temperature limits are exceeded; therefore, Prysmian Group recommends storing I/O cables in appropriate temperature conditions ≥ 24 hours prior to placement.

Temperature Range

Shipping and Storage: (Riser) -40° F to +176° F (-40° C to +80° C)
 (Plenum) -40° F to +176° F (-40° C to +80° C)

Installation: (Riser) +14° F to +140° F (-10° C to +60° C)
 (Plenum) +32° F to +140° F (0° C to +60° C)

Operation: (Riser) -40° F to +176° F (-40° C to +80° C)
 (Plenum) -40° F to +176° F (-40° C to +80° C)

Ordering Guide

The Prysmian Group part number incorporates several significant attributes involving cable design and optical performance. The appropriate part number can be configured using the process described in the example.

ezDISTRIBUTION™ I/O Tight Buffered

Riser and plenum cables

INDOOR/OUTDOOR
TIGHT BUFFER

Example: ezDISTRIBUTION tight buffered | i/O riser (OFNR/FT4), 12 fiber subunits | 48 62.5/125 multimode fibers total (printed in feet)

1 LENGTH MARKINGS	2 PRODUCT FAMILY	3 CONSTRUCTION	4 FIBER GROUPING	5 FIBER TYPE	6 FIBER COUNT	7 FIBER GRADE
F	C1181	BLANK	12	G6	048	M2

PART NUMBER CONSTRUCTION	
1 LENGTH MARKINGS	F = Feet or M = Meters
2 PRODUCT FAMILY	ezDISTRIBUTION INDOOR / OUTDOOR Riser-FT4 C1181 = ezDISTRIBUTION Indoor/Outdoor Riser Tight Buffer Flame Rating: OFNR/FT4 Fiber Count 2 to 144 Plenum-FT6 C1182 = ezDISTRIBUTION Indoor/Outdoor Plenum Tight Buffer Flame Rating: OFNP/FT6 Fiber Count 2 to 96
3 CONSTRUCTION	(blank) = none AJ = Jacketed Aluminum SJ = Jacketed Steel
4 FIBER GROUPING	00 = single-unit 06 = 6f per subunit 12 = 12f per subunit

FIBER INFORMATION				
5 FIBER TYPE				
SINGLE-MODE				
ES = Enhanced Single-Mode (ITU G.652 C & D)				
BB = Bend-Insensitive Single-Mode (ITU G.657.A1 & G.652.D)				
BX = Bend-Insensitive Single-Mode (ITU G.657.A2 & B2 & G.652.D)				
MULTIMODE				
	Wavelength (nm)	Bandwidth (MHz)	1 GbE Dist (m)	10 GbE Dist (m)
G6 = OM1 (62.5µm)	850/1300	200/500	300/550	33/___
G5 = OM2+ (50µm)	850/1300	700/500	800/550	150/___
G3 = OM3 (50µm)	850/1300	1500/500	1000/550	300/___
G4 = OM4 (50µm)	850/1300	3500/500	1100/550	550/___
6 FIBER COUNT				
002 to 144 fibers -Riser				
002 to 096 fibers -Plenum				
7 FIBER GRADE				
SINGLE-MODE				
Attenuation (dB/km)	Wavelength (nm)	Fiber Type		
EB = 0.7/0.7/0.7	1310/1383/1550	Enhanced Single-Mode		
EA = 0.5/0.5/0.5	1310/1383/1550	Bend-Insensitive Single-Mode		
E7 = 0.4/0.4/0.3	1310/1383/1550	Bend-Insensitive Single-Mode		
MULTIMODE				
Attenuation (dB/km)	Wavelength (nm)	Fiber Type		
M2 = 3.5/1.0	850/1300	OM1 (62.5µm)		
M3 = 3.0/1.0	850/1300	OM2+, OM3, OM4 (50µm)		
Other cable constructions and fiber performance grades available on request.				