

## **WPS-NF**

Weather Protection System: N Female Antenna Port/ Device Seal



Installation instructions


Installation instructions

Image: State of the sta

| General             | Specification            | Comment |
|---------------------|--------------------------|---------|
| Ports supported     | See figure below.        |         |
| Dimensions in. (mm) | 1.10 x .43 (27.9 x 10.8) |         |
| Weight              | 0.01 lb   5.4 g          |         |
| Material            | Silicone rubber          |         |
| Reusability         | Unlimited                |         |

| Environmental            | Specification   | Comment                         |
|--------------------------|---|---------------------------------|
| Installation temperature | -40 °C to +65 °C (-40 °F to 149 °F)   |                                 |
| Operating temperature    | -40 °C to +65 °C (-40 °F to 149 °F)   |                                 |
| Storage temperature      | -55 °C to +85 °C (-67 °F to 185 °F)   |                                 |
| Moisture resistance      | No leakage  | ANSI/SCTE 60 2004, IP-67, IP-68 |
| Corrosion resistance     | 1000 hours  | ASTM B117                       |
| U.V. resistance          | Exposure to UV light for 1000<br>hours per ASTM G 53 using UVB-<br>313 type lamps |                                 |
| H.A.L.T.                 | 40 hours  |                                 |
| Fire rating              | UL94 HB   |                                 |

## WPS-NF COMPATIBLE PORT SPECIFICATION



07/03/19

©2019 JMA Wireless. All rights reserved. This document contains proprietary information. All products, company names, brands, and logos are trademarks™ or registered® trademarks of their respective holders. All specifications are subject to change without notice. +1 315.431.7100 customerservice@jmawireless.com

