



## WK-CNT

**Weatherproofing Kit for Connectors and Splices, includes butyl rubber and PVC tape**

### Dimensions

Nominal Size 0.195 in | 0.240 in | 0.300 in | 0.400 in | 0.600 in

### General Specifications

Application	Provides additional moisture seal for cable connections
Applications per Kit	Four 0.195 in to 0.195 in   Four 0.240 in to 0.240 in   Three 0.300 in to 0.300 in   Three 0.400 in to 0.300 in   Three 0.400 in to 0.400 in   Two 0.400 in to 0.600 in   Two 0.600 in to 0.600 in
Includes	One roll of 2-1/2 in butyl rubber tape (0.06 in thick)   One roll of 3/4 in PVC tape
Material Type	Butyl rubber tape   PVC tape
Ordering Note	CommScope® non-standard product
Package Quantity	1

### Mechanical Specifications

UV Resistance Test Method	Butyl test method in QUV weatherometer cycle of 8 hours UV at 150 °F then 4 hours of condensation at 104 °F   PVC tape test method UL 510, ASTM D1000
UV Resistance, minimum with no degradation	=1000 hours
Weather Resistance Test Method	04AS00-03.6.0   MIL-STD-1344A, Method 1002

### Packed Dimensions

Height	16.5 cm   6.5 in
Length	9.2 cm   3.6 in
Shipping Weight	0.36 kg   0.80 lb
Width	5.1 cm   2.0 in

### Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

### Included Products

42615-10 — Butyl Rubber Tape, 24 in

9905-41 — Black 3/4 in PVC Tape, 66 ft