

Specification Sheet

Part Number: T250R0X2



Heavy Duty Cable Tie, 20" Long, UL Rated, 250lb Tensile Strength, PA66, Black, 25/pkg

Article Number 111-24801

Type T250R

Color Black (BK)

Features & Benefits

- Engineered and manufactured for maximum performance and quality.
- Made from 100% high-quality plastic to ensure efficient recycling.
- Inside serration for a strong grip onto bundles.
- Easy application either manually or with a tensioning tool.

Quantity Per bag

Product Description

Heavy duty T-Series cable ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

| | |
|--|---|
| Short Description | Heavy Duty Cable Tie, 20" Long, UL Rated, 250lb Tensile Strength, PA66, Black, 25/pkg |
| Global Part Name | T250R-PA66-BK |
| Minimum Tensile Strength (Imperial) | 250.0 |
| Minimum Tensile Strength (Metric) | 1115.0 |
| Length L (Imperial) | 20.0 |
| Length L (Metric) | 515.0 |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.49 |
| Width W (Metric) | 12.4 |
| Bundle Diameter Min (Imperial) | 0.47 |
| Bundle Diameter Min (Metric) | 12.0 |
| Bundle Diameter Max (Imperial) | 4.92 |

| | |
|--|----------------------------------|
| Bundle Diameter Max (Metric) | 125.0 |
| Thickness T (Metric) | 1.9 |
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL 94 V2 |
| Halogen free | Yes |
| Operating Temperature (Metric) | -40°F to +185°F (-40°C to +85°C) |
| ROHS Complaint | Yes |
| Certification/Specification WEB | UL-ZODZ2.E64139 |
| UL Recognized (US) | Yes |
| UL Listed (US and Canada) | Yes |
| UL Recognized (US and Canada) | Yes |
| UL Listed (US) | Yes |
| Package Quantity(Imperial) | 25 |

Package Quantity (Metric) 25

Customs Number 3926909988

Content Unit(BMEcat) pcs.