



Class 3 Eclipse™ Coat

Stock Number - C44129

Compliance Standards: ANSI/ISEA 107 Type R, Class 3; ASTM F1891



Garment Detail: Coats are set-in sleeve construction with full cut shoulder and 180 degree sleeve-to-body angle. The coat has a zippered storm fly front with snap closure and an attached hood-in-collar. Sleeve cuffs have hook and loop take-up straps. The coat has a full vented cape back with fall protection access and 2 front cargo pockets with closure.

Garment Type: High visibility, liquid proof, and flame and arc resistant coat.

Reflective Tape: ANSI/ISEA 107 compliant 2" FR silver glass bead tape.

Sizes: S, M, L, XL, 2X, 3X, 4X

Color: Fluorescent Orange-Red.

Configuration: Harness tape layout with 1 horizontal band on body and 2 bands on each sleeve.

Material: Fluorescent orange-red material is 10.3 oz./yd² FR PVC on non-woven Nomex® with Thermo-Grid™ technology.

Labels/Tags:

1. Woven label sewn at neck displays Tingley logo and size.
2. Eclipse logo on sleeve cuff take-up.
3. Label sewn into left front hem displays ANSI/ISEA 107, ASTM F1891 and NFPA 70E compliance. Care instructions, fabric composition, lot and date codes are located on the reverse.
4. Label sewn into left front hem displays warning/disclaimer.
5. Name tag is sewn into left front hem.
6. Job Sight FR™ brand and CAT 2 heat transfer label on right pocket closure flap.
7. Printed hangtag with style, size, UPC bar code and noting high visibility, waterproof, and flame and arc resistance.

Seam Construction: All seams are 100% waterproof RF/heat sealed lap construction.

Closure Type: Zippered storm fly front with concealed snap closure system.

Packaging: Printed polyethylene bag.

Pockets: Two front cargo pockets with flap, and hook and loop closures.

Other: Thermal Performance conforms to ASTM F1891, Test Method ASTM F1959.

Eclipse Orange-Red ARC Rating: 11 cal/cm².

Dimensions	S	M	L	XL	2X	3X	4X
Chest	46"	50"	54"	58"	62"	66"	70"
Length	47"	48"	50"	50"	52"	52"	52"
Sleeve Length	36"	36"	36.5"	37"	37.5"	38"	38"

Case Pack: 12 each

Case Dimensions/Weight

S = 15"(L) X 12"(W) X 20"(H) / 37 lbs.

2X = 15"(L) X 12"(W) X 20"(H) / 46 lbs.

M = 15"(L) X 12"(W) X 20"(H) / 40 lbs.

3X = 15"(L) X 12"(W) X 20"(H) / 48 lbs.

L = 15"(L) X 12"(W) X 20"(H) / 42 lbs.

4X = 15"(L) X 12"(W) X 20"(H) / 51 lbs.

XL = 15"(L) X 12"(W) X 20"(H) / 44 lbs.

Eclipse™, Thermo-Grid™ and Job Sight FR™ are trademarks of Tingley Rubber Corp.

Nomex® is a registered trademark of E. I. du Pont de Nemours and Co.