

## A3 Extra Fine Tip Paint Marker



### SPECIFICATIONS

- Item # : 10101XFL Black  
10102XFL Blue  
10103XFL Green  
10104XFL Red  
10105XFL White  
10106XFL Yellow  
10100FXL Repl. Tip

- Style: Valve Activated
- Tip Type: Extra-Fine
- Marking Width: 1 mm. (0.04")
- Dimensions: 5 1/4" L x 7/16" Ø (133 x 11 mm.) \*
- Marking Temp. Range: -50° to 150° Fahrenheit (-45° to 65° C)
- Dry Time: approx. 30 sec.
- Quantity/ Weight Per Box: 12ea./ 0.25 lb./ (115 g.)
- Quantity/ Weight Per Case: 144ea./ 3.5 lb./ (1.6 kg.)
- **Directions For Use:** Shake well with cap on. Hold marker tip upward and press down once to release any pressure that may have built up during transportation. Gently press tip until inked. Replace cap after use.

\* Dimensions taken w/ marker capped.

### PRODUCT FEATURES

- Heavy duty, metal supported polyester tip allows for precise, consistent and dependable extra-fine line marking.
- Permanent, xylene free paint.
- Heavy -duty aluminum barrel withstands industrial use.
- Press-tip valve regulates paint flow.

### TYPICAL USES

- Especially suited for precise, readable marking on small surfaces.
- Quality control, laboratories, parts identification, small tags and labels.
- Highly visible and permanent on most surfaces such as metals, plastics, wood, glass, ceramics, textiles, poster-board, etc.

### SAFETY INFORMATION

- Read MSDS before using (available online at [www.umarkers.com](http://www.umarkers.com)).
- Conforms to ASTM D 4236.
- Keep out of reach of children. For professional use only.

