

# EVOLUTION™ 6100 FULL BRIM



## TOUGH HDPE SHELL

With a full brim providing additional protection against sun, glare, rain and falling debris.



## VENTILATION OPTION

Vented versions are available to reduce inside helmet temperature. (ANSI Class C)



## SUPREME COMFORT

A 6-point suspension with polyester textile straps and a unique 3D Adjustment harness depth setting.

**PIP** SALES PARTNER



Represented exclusively by:  
Protective Industrial Products Inc  
Albany, NY USA 12205  
1-800-262-5755

# EVOLUTION 6161 Full Brim Revolution™ Wheel Ratchet

EVO6161 with textile suspension and Revolution™ wheel ratchet. Conforming to ANSI/ISEA Z89.1-2009 Type I, Class E.



# EVOLUTION 6141 Full Brim EasyJust™ Slip Ratchet

EVO6141 with textile suspension and EasyJust™ slip ratchet. Conforming to ANSI/ISEA Z89.1-2009 Type I, Class E.



ITEM #	DESCRIPTION	CASE QTY
280-EV6161-10	EVO6161, FB, Non Vented, - White	10
280-EV6161-20	EVO6161, FB, Non Vented, - Yellow	10
280-EV6161-30	EVO6161, FB, Non Vented, - Green	10
280-EV6161-50	EVO6161, FB, Non Vented, - Blue	10
280-EV6161-60	EVO6161, FB, Non Vented, - Red	10
280-EV6161-LY	EVO6161, FB, Non Vented, - Bright Lime/Green	10
280-EV6161-OR	EVO6161, FB, Non Vented, - Bright Orange	10
280-EV6161V-10	EVO6161, FB, Vented, - White (Class C)	10
280-EV6161V-20	EVO6161, FB, Vented, - Yellow (Class C)	10

ITEM #	DESCRIPTION	CASE QTY
280-EV6141-10	EVO6141, FB, Non Vented, - White	10
280-EV6141-20	EVO6141, FB, Non Vented, - Yellow	10
280-EV6141-30	EVO6141, FB, Non Vented, - Green	10
280-EV6141-50	EVO6141, FB, Non Vented, - Blue	10
280-EV6141-60	EVO6141, FB, Non Vented, - Red	10
280-EV6141-LY	EVO6141, FB, Non Vented, - Bright Lime/Green	10
280-EV6141-OR	EVO6141, FB, Non Vented, - Bright Orange	10
280-EV6141V-10	EVO6141, FB, Vented, - White (Class C)	10
280-EV6141V-20	EVO6141, FB, Vented, - Yellow (Class C)	10



## Retractable Safety Eyewear

Easy assembly kit for adding a clear or gray anti-scratch/anti-fog lens, that retracts into the shell of an Evolution Deluxe 6100 hard hat when not in use. Meets ANSI Z87.1-2010 requirements.



PERFORMANCE		TEMPERATURE RESISTANCE		SHELL MATERIAL		OPTIONS			SUSPENSION OPTIONS			CHINSTRAP OPTIONS	
Impact Resistance 54 JOULES	Electrical Insulation	+120°F +50°C	-22°F -30°C	HDPE	Recyclable	Ventilated	CR2 Reflective Decal Kit	Integrated Eyewear	Wheel Ratchet	Slip Ratchet	Textile Webbing	4 pts	2 pts
✓	NON-VENTED VERSION	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓



Represented exclusively by:  
Protective Industrial Products Inc  
Albany, NY USA 12205  
1-800-262-5755