


JOB NAME: _____

DATE: _____

TYPE: _____



DIMENSIONS:



XT-CWP-RG-EM
XT-CWP-GG-EM

Wet Location Combination Exit Sign & Emergency

High impact thermoplastic energy-efficient LED exit with emergency battery backup

Standard



Optional



ELECTRICAL SPECIFICATIONS:

- Dual 120/277 voltage
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- 6V long-life, maintenance-free, rechargeable NiCd battery
- Internal solid-state transfer switch automatically connects the internal battery to LED board/lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours

LIGHTING SPECIFICATIONS:

- Two fully-adjustable 5.4 watt, glare-free lamp heads
- High-performance reflector and tempered glass lens for optimal light distribution
- Ultra-bright, energy efficient, long-life Red or Green LED exit sign illumination

HOUSING SPECIFICATIONS:

- 5VA flame retardant, UV-stabilized polycarbonate gray finish
- High-impact resistant, UV-stabilized polycarbonate clear lens
- Corrosion-resistant enclosure engineering grade silicone gasket
- Top and side K/O's provided for conduit feed applications
- EZ snap-out Chevron directional indicators

MOUNTING:

- Mounting hardware provided for back surface wall mount

WARRANTY:

- Five-year warranty on all electronics and housing
- Battery pro-rated for five years

CERTIFICATIONS:

- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, local and state codes



JOB NAME: _____

DATE: _____

TYPE: _____

XT-CWP-RG-EM
XT-CWP-GG-EM

Wet Location Combination Exit Sign & Emergency

ORDER INFORMATION:

MODEL	LETTERS	FACEPLATE	TRIMPLATE	VOLTAGE	BATTERY	CUSTOMIZE
XT-CWP-RG-EM	Red	Universal Single/Double	Gray	120/277	Ni-Cad	Black housing
XT-CWP-GG-EM	Green	Universal Single/Double	Gray	120/277	Ni-Cad	Black housing

ELECTRICAL INFORMATION:

MODEL NO	INPUT WATTS (W)	INPUT WATTS (W)	INPUT AMPS (A)	INPUT AMPS (A)
	120V	277V	120V	277V
XT-CWP-RG-EM	7.2	7.7	0.063	0.030

