

# TINGLEY

est. 1896

## Premier G2® Composite Safety Toe Knee Boot

**Style Number - 93255**

**Compliance Standards:** ASTM F2413 M/I/C EH\*  
ASTM F3445 SR  
ASTM F1671 Viral Penetration



**Product Detail:** Composite safety toe does not transfer cold or set off metal detectors. Injection molded seamless construction provides 100% liquidproof protection. Calf Relief Expansion (CRE)<sup>™</sup> expands up to 1.5 inches for more calf comfort. Soft and flexible upper for all day working comfort. Slip resistant per ASTM F3445, the standard specification as of July 2021.

\*Electrical Hazard soles and heels are intended to reduce hazards due to accidental contact with live electrical circuits, electrically energized conductors, parts or apparatus. They are not intended for work environments where volatile chemicals or explosives may be present, where conductive footwear is required.

**Warning:** Electric Hazard features of the soles and heels will deteriorate in wet environments, and when worn with excessive wear on the soles and heels.

**Product Type:** Knee Boot

**Insole:** Extra thick, removable contour cushion insoles absorb moisture and shock, and provide outstanding comfort.

**Sizes:** US Men's 3 through 14

**Outsole Tread Pattern:** Chevron-Plus® outsole provides excellent slip resistance on wet-contaminated and wet-clean surfaces.

**Color:** Brick Red Upper / Crème Outsole

**Appearance:** Boots are clean and free from obvious defects, flash and contamination. The surfaces are visually consistent in texture and contrast with no evidence of foreign material or distortion. Molded products are fully formed, well defined and properly aligned, with level outsoles, smooth seams and neatly trimmed edges. Colors are consistent within and between lots.

**Material:** High Molecular Weight PVC (polyvinyl chloride) with Specialty Additives

**Closure Type:** None

**Labeling:** Lot code, country of origin, and size are marked on the outsoles. Boots are labeled to indicate compliance with ASTM F2413, F3445 and California Prop 65.

**Packaging:** Boots are pair packed in a clear plastic, draw-string bag and labeled for individual sale. Packaged six (6) pairs per labeled, corrugated cardboard case.

**Applications:** Suited for various jobs within Food Processing (particularly red meat, turkey, dairy, and beverage), Chemical, and Petroleum Industries.

**Chemical Resistance:** Fats, oils, certain acids, alkalis, petroleum hydrocarbons, and other chemicals.

**Country of Origin:** China

**Other:** Testing and certification documents are available upon request from Tingley Rubber Corporation.

Dims & Weight by Size:	M3 W5	M4 W6	M5 W7	M6 W8	M7 W9	M8 W10	M9 W11	M10 W12
Height (in.)	14.3	14.4	14.6	14.6	14.9	15.1	15.3	15.6
Ball Width (in.)	3.8	3.9	3.9	4.0	4.1	4.1	4.2	4.3
Heel-to-Toe (in.)	10.0	10.3	10.6	11.0	11.3	11.7	11.9	12.1
Topline Circumference (in.)	16.4	16.7	17.0	17.1	17.4	17.7	18.1	18.6
Weight (lbs)	4.2	4.4	4.6	4.8	5.1	5.1	5.5	5.7

Dims & Weight by Size:	M11 W13	12	13	14
Height (in.)	15.7	15.9	16.0	16.2
Ball Width (in.)	4.3	4.4	4.5	4.6
Heel-to-Toe (in.)	12.4	12.7	13.1	13.3
Topline Circumference (in.)	18.7	19.0	19.3	19.9
Weight (lbs)	6.0	6.2	6.6	6.8

**Case Pack:** 6 pairs

**Package Dimensions:**

		Case Carton (L x W x H)
Sizes 3 to 5		17 x 16 x 12 in
Sizes 6 to 8		17 x 17 x 12 in
Sizes 9 to 11		19 x 19 x 13 in
Sizes 12 to 14		20 x 19 x 13 in