

TINGLEY

est. 1896

Profile® Composite Safety Toe Knee Boot

Style Number - 51254

Compliance Standards: ASTM F2413 M/IC
ASTM F3445 SR



Product Detail: Composite safety toe does not transfer cold or set off metal detectors. Injection molded seamless construction provides 100% liquidproof protection. Calf Relief Expansion (CRE)™ expands up to 1.5 inches for more calf comfort. Flexible upper material stays supple in cold temperatures to make walking easier. Outsole is soft for slip resistance and absorbs shock when walking. Slip resistant per ASTM F3445, the standard specification as of July 2021.

Product Type: Knee Boot

Insole: Removable polyurethane, contour insole features three layers to wick perspiration, promote faster drying and absorb shock for all day comfort.

Sizes: US Men's 3 through 14

Outsole Tread Pattern: Cleated outsole spits out debris for excellent gripping action.

Color: Dark Brown Upper / Beige Outsole

Appearance: Boots are clean and free from obvious defects, flash and contamination. The surfaces are visually consistent in texture and contrast with no evidence of foreign material or distortion. Molded products are fully formed, well defined and properly aligned, with level outsoles, smooth seams and neatly trimmed edges. Colors are consistent within and between lots.

Material: High Quality PVC (polyvinyl chloride) with Frigiflex® low temperature additives

Closure Type: None

Labeling: Lot code, country of origin, and size are marked on the outsoles. Printed hangtag displays name, style, and product features and benefits. Boots are labeled to indicate compliance with ASTM F2413, F3445 and California Prop 65.

Packaging: Boots are pair packed with a plastic fastener strung through a pre-punched hole in the hangtag. Packaged six (6) pairs per labeled, corrugated cardboard case.

Applications: Suited for various jobs within Farm and Barn, Agriculture and Industry, Municipalities, and some Food Processing.

Chemical Resistance: Fats, certain acids, alkalies, hydrocarbons and other chemicals.

Country of Origin: China

Other: Testing and certification documents are available upon request from Tingley Rubber Corporation.

Dims & Weight by Size:	M3 W5	M4 W6	M5 W7	M6 W8	M7 W9	M8 W10	M9 W11	M10 W12
Height (in.)	14.3	14.4	14.6	14.6	14.9	15.1	15.3	15.6
Ball Width (in.)	3.8	3.9	3.9	4.0	4.1	4.1	4.2	4.3
Heel-to-Toe (in.)	10.0	10.3	10.6	11.0	11.3	11.7	11.9	12.1
Topline Circumference (in.)	16.4	16.7	17.0	17.1	17.4	17.7	18.1	18.6
Weight (lbs)	4.2	4.4	4.6	4.8	5.1	5.1	5.5	5.7

Dims & Weight by Size:	M11 W13	12	13	14
Height (in.)	15.7	15.9	16.0	16.2
Ball Width (in.)	4.3	4.4	4.5	4.6
Heel-to-Toe (in.)	12.4	12.7	13.1	13.3
Topline Circumference (in.)	18.7	19.0	19.3	19.9
Weight (lbs)	6.0	6.2	6.6	6.8

Case Pack: 6 pairs

Package Dimensions:

	Case Carton (L x W x H)
Sizes 3 to 5	17 x 16 x 12 in
Sizes 6 to 8	17 x 17 x 12 in
Sizes 9 to 11	19 x 19 x 13 in
Sizes 12 to 14	20 x 19 x 13 in